

FLOOR machine line

The RWS models are the floor machine line, which are in two versions available. This machines also have the RUFF modular system with 19 interchangeable winding heads and 10 roller tables for the largest flexibility. The sturdy construction with highest precision in production and best quality of material guaranties reliability and very long lifetime of the machines.

FLOOR machine line RWS

Models RWS-GLOBAL, RWS-EVOLUTION, RWS-GLOBAL-SHUTTLE, RWS-EVO-SHUTTLE, RWS-TAPE, RWS-Evolution-Tape

18 interchangeable heads

9 gear rack heads	RW 33 RW 45-380	RW 44-1 RW 45-EH	RW 44-1V RW 44-RZ	RW 45 RW 45-VRZ	RW 45-V
1 side slider winding head	RW 50				
8 taping heads	RW 33/B, RW 44-RZ/B	RW 44/1B, RW 45-VRZ/B	RW 45/B, RW 45-VRZ/B-380	RW 45-380/BU,	RW 45/BU
1 magazine less winding head	RW 05-ML				

10 interchangeable tables	RW 333 RW 333-V-13	RW 333-V RW 444	RW 333- PML	RW 333-V-SO RW 444-P	RW 333-VS1 RW 444-PSR	RW 333-VS2
---------------------------	-------------------------------------	----------------------------------	------------------------------	---------------------------------------	--	-------------------

Capability ranges

wire Ø monofilar	0.4 - 4.5 mm	tape size	9 - 25 mm
wire Ø bifilar	bis 2 x 2.8 mm	machine size	approx. 1100 x 700 mm Shuttle: 2000 x 700 mm
finished core OD	65 - 2800 mm	machine weight	approx. 200 kg
finished core ID	up from 25 mm		
finished core H	up to 380 mm		
compressed air	6 bar		

Model RWS-Global

The RWS-Global is for standard winding applications. The new NC controller with touch screen is user friendly and it is very easy to understand. Just a few inputs are needed for create a winding program. All standard winding methods are available e.g.: Tape-/Wire winding, Index, Reverse winding. Several winding sequences can be written in one winding program. So for example different pitch and index etc. More than 200 programs

can be saved on this control. All languages in Latin characters are available on this controller.



controller	5.7" monochrom touchpanel
language	all Latin characters
winding head	three phase motor with inverter
roller table	servo motor
supply voltage	1 PH / 230 V / 16 A